



F100BETL/F100BETX

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F100BETX
MOTOR	
Displacement (cc)	1596
Architecture	L4
Bore x Stroke (mm)	79.0 X 81.4
Full throttle operating range (tr/min)	5000-6000
Fuel	Wet Sump
Fuel consumption (L/h-tr/min)	31.9 L/h @5500 r/min
Lubrication system	Unleaded
Power system	4 carburetors
Reduction ratio	8.9 :1
Number of Displacement	-
Maximum Power (Kw)	-
Ignition System	Electronic Ignition (TCI)
Gear Ratio	-
Steering Control	-
Reverse direction	-
Trim method (positions)	-
Engine Type	In-line 4
Start-up	Electric with Prime Start™
Max.Prop Shaft Horsepower (Kw)	73.6 (100 hp)
MORE	
Control	Remote Control
Alternator	20 A
Propeller Rotation	Clockwise
DIMENSIONS	
Engine Oil Capacity (L)	-
Oil capacity (L)	3.7 L / 3.5 L
Engine transom height (mm)	X : 643 (25.3 inch)
Dry weight with propeller (kg)	188
EQUIPMENT	
Service kit assy.	✓
Fuel Tank comp.	-
Fuel Pipe Comp.	✓
Remocon Control	✓
14ft Cable Remocon	-
15ft Cable Remocon	-

20ft Cable Remocon	-
Cable end, Remote control	-
Tachometer	✓
Trim Meter	-
Panel Switch	-
Ride, Guide Kit Twin	-
Multi Display	-
Speedo Assy.	-
Fuel Meter Movement	-
Kill Switch	-
REGULAR PROPELLER (3 blades)	F100BETX
Material	ALUMINUM
Diameter	13 1/2

Always wear a helmet, eye protection and protective proper clothing.

YAMAHANIGERIA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

